



7 SPACE (7/16") STAINLESS STEEL GRATING LOAD TABLE

Use this table when evaluating spans and loads of the following types of stainless steel grating: **7-SLS-4, 7-SLS-2, 7-DTS-4, 7-DTS-2**

Bearing Bar Size (inches)	Approx. Weight psf *	Max. Ped. Span**	Sec. Prop. Sx in ³ lx in ⁴	Unsupported Span												
				2'-0	2'-6	3'-0	3'-6	4'-0	4'-6	5'-0	5'-6	6'-0	6'-6	7'-0	8'-0	9'-0
3/4 x 3/16	13.9	4'-10"	0.482 0.181	U	1,607	1,029	714	525	402	318	257	All loads and deflections are theoretical and based upon the gross sections of the bearing bars, using a fiber stress of 20,000 psi.				
				D	0.114	0.179	0.257	0.350	0.457	0.579	0.714					
				C	1,607	1,286	1,071	918	804	714	643	The values are not intended to be absolute since the actual load capacity will be affected by the slight variations in mill and manufacturing tolerances. Grating for spans to the left of the heavy line have a deflection ≤ 1/4" for uniform loads of 100 psf.				
				D	0.091	0.143	0.206	0.280	0.366	0.463	0.571					
1 x 1/8	12.4	5'-5"	0.571 0.286	U	1,905	1,219	847	622	476	376	305	252				
				D	0.086	0.134	0.193	0.263	0.343	0.434	0.536	0.648				
				C	1,905	1,524	1,270	1,088	952	847	762	693				
				D	0.069	0.107	0.154	0.210	0.274	0.347	0.429	0.519				
1 x 3/16	18.3	6'-0"	0.857 0.429	U	2,857	1,829	1,270	933	714	564	457	378	318	271		
				D	0.086	0.134	0.193	0.263	0.343	0.434	0.536	0.648	0.771	0.905		
				C	2,857	2,286	1,905	1,633	1,429	1,270	1,143	1,039	952	879		
				D	0.069	0.107	0.154	0.210	0.274	0.347	0.429	0.519	0.617	0.724		
1-1/4 x 1/8	15.3	6'-5"	0.893 0.558	U	2,976	1,905	1,323	972	744	588	476	394	331	282		
				D	0.069	0.107	0.154	0.210	0.274	0.347	0.429	0.519	0.617	0.724		
				C	2,976	2,381	1,984	1,701	1,488	1,323	1,191	1,082	992	916		
				D	0.055	0.086	0.123	0.168	0.219	0.278	0.343	0.415	0.494	0.579		
1-1/4 x 3/16	22.7	7'-1"	1.339 0.837	U	4,464	2,857	1,984	1,458	1,116	882	714	590	496	423	364	279
				D	0.069	0.107	0.154	0.210	0.274	0.347	0.429	0.519	0.617	0.724	0.840	1.097
				C	4,464	3,571	2,976	2,551	2,232	1,984	1,786	1,623	1,488	1,374	1,276	1,116
				D	0.055	0.086	0.123	0.168	0.219	0.278	0.343	0.415	0.494	0.579	0.672	0.878
1-1/2 x 1/8	18.3	7'-4"	1.286 0.964	U	4,286	2,743	1,905	1,399	1,071	847	686	567	476	406	350	268
				D	0.057	0.089	0.129	0.175	0.229	0.289	0.357	0.432	0.514	0.604	0.700	0.914
				C	4,286	3,429	2,857	2,449	2,143	1,905	1,714	1,558	1,429	1,319	1,225	1,071
				D	0.046	0.071	0.103	0.140	0.183	0.231	0.286	0.346	0.411	0.483	0.560	0.731
1-1/2 x 3/16	27.2	8'-2"	1.929 1.446	U	6,429	4,114	2,857	2,099	1,607	1,270	1,029	850	714	609	525	402
				D	0.057	0.089	0.129	0.175	0.229	0.289	0.357	0.432	0.514	0.604	0.700	0.914
				C	6,429	5,143	4,286	3,674	3,214	2,857	2,571	2,338	2,143	1,978	1,837	1,607
				D	0.046	0.071	0.103	0.140	0.183	0.231	0.286	0.346	0.411	0.483	0.560	0.731
1-3/4 x 1/8	21.3	8'-3"	1.750 1.531	U	5,833	3,733	2,593	1,905	1,458	1,152	933	771	648	552	476	365
				D	0.049	0.077	0.110	0.150	0.196	0.248	0.306	0.370	0.441	0.517	0.600	0.784
				C	5,833	4,667	3,889	3,333	2,917	2,593	2,333	2,121	1,944	1,795	1,667	1,458
				D	0.039	0.061	0.088	0.120	0.157	0.198	0.245	0.296	0.353	0.414	0.480	0.627
1-3/4 x 3/16	31.6	9'-2"	2.625 2.297	U	8,750	5,600	3,889	2,857	2,188	1,728	1,400	1,157	972	828	714	547
				D	0.049	0.077	0.110	0.150	0.196	0.248	0.306	0.370	0.441	0.517	0.600	0.784
				C	8,750	7,000	5,833	5,000	4,375	3,889	3,500	3,182	2,917	2,692	2,500	2,188
				D	0.039	0.061	0.088	0.120	0.157	0.198	0.245	0.296	0.353	0.414	0.480	0.627
2 x 1/8	24.3	9'-2"	2.286 2.286	U	7,619	4,876	3,386	2,488	1,905	1,505	1,219	1,008	847	721	622	476
				D	0.043	0.067	0.096	0.131	0.171	0.217	0.268	0.324	0.386	0.453	0.525	0.686
				C	7,619	6,095	5,079	4,354	3,810	3,386	3,048	2,771	2,540	2,344	2,177	1,905
				D	0.034	0.054	0.077	0.105	0.137	0.174	0.214	0.259	0.309	0.362	0.420	0.549
2 x 3/16	36.0	10'-1"	3.429 3.429	U	11,429	7,314	5,079	3,732	2,857	2,258	1,829	1,511	1,270	1,082	933	714
				D	0.043	0.067	0.096	0.131	0.171	0.217	0.268	0.324	0.386	0.453	0.525	0.686
				C	11,429	9,143	7,619	6,531	5,714	5,079	4,571	4,156	3,810	3,517	3,265	2,857
				D	0.034	0.054	0.077	0.105	0.137	0.174	0.214	0.259	0.309	0.362	0.420	0.549
2-1/4 x 3/16	40.5	11'-1"	4.339 4.882	U	14,464	9,257	6,429	4,723	3,616	2,857	2,314	1,913	1,607	1,369	1,181	904
				D	0.038	0.060	0.086	0.117	0.152	0.193	0.238	0.288	0.343	0.402	0.467	0.610
				C	14,464	11,571	9,643	8,265	7,232	6,429	5,786	5,260	4,821	4,451	4,133	3,616
				D	0.030	0.048	0.069	0.093	0.122	0.154	0.190	0.230	0.274	0.322	0.373	0.488
2-1/2 x 3/16	44.9	12'-0"	5.357 6.696	U	17,857	11,429	7,937	5,831	4,464	3,527	2,857	2,361	1,984	1,691	1,458	1,116
				D	0.034	0.054	0.077	0.105	0.137	0.174	0.214	0.259	0.309	0.362	0.420	0.549
				C	17,857	14,286	11,905	10,204	8,929	7,937	7,143	6,494	5,952	5,495	5,102	4,464
				D	0.027	0.043	0.062	0.084	0.110	0.139	0.171	0.207	0.247	0.290	0.336	0.439

* Weight per square foot based upon 7-SLS-4 grating. Add .30 psf for 2" on center cross bars. ** Maximum pedestrian load is defined as a 100# uniform load with deflection ≤ 1/4 inch. (The 1/4" maximum deflection criteria is considered consistent with pedestrian comfort, but may be exceeded for other loading conditions at the discretion of the specifying authority.) *** Section properties per foot of width.

Note: When gratings with serrated surface are specified, the depth of the grating required for a specific load will be 1/4" greater than that shown in these tables.

Panel Widths

Grating panels are available from stock in nominal 24" and 36" widths. When considering alternative widths, consult this table to select widths that will maintain uniform "out-to-out" spacing of the bearing bars. Specified widths deviating from this table will be fabricated to size with side banding and the bar spacing on one side of the finished panel will vary from the spacing throughout the remainder of the panel.

Number of Bearing Bars	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Panel Width	5/8"	1-1/16"	1-1/2"	1-15/16"	2-3/8"	2-13/16"	3-1/4"	3-11/16"	4-1/8"	4-9/16"	5"	5-7/16"	6-5/16"	6-3/4"	
Number of Bearing Bars	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Panel Width	7-3/16"	7-5/8"	8-1/16"	8-1/2"	8-15/16"	9-3/8"	9-13/16"	10-1/4"	10-11/16"	11-1/8"	11-9/16"	12"	12-7/16"	12-7/8"	13-5/16"
Number of Bearing Bars	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46
Panel Width	13-3/4"	14-3/16"	14-5/8"	15-1/16"	15-1/2"	15-15/16"	16-3/8"	16-13/16"	17-1/4"	17-11/16"	18-1/8"	18-9/16"	19"	19-7/16"	19-7/8"
Number of Bearing Bars	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61
Panel Width	20-5/16"	20-3/4"	21-3/16"	21-5/8"	22-1/16"	22-1/2"	22-15/16"	23-3/8"	23-13/16"	24-1/4"	24-11/16"	25-1/8"	25-9/16"	26"	26-7/16"
Number of Bearing Bars	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76
Panel Width	26-7/8"	27-5/16"	27-3/4"	28-3/16"	28-5/8"	29-1/16"	29-1/2"	29-15/16"	30-3/8"	30-13/16"	31-1/4"	31-11/16"	32-1/8"	32-9/16"	33"
Number of Bearing Bars	77	78	79	80	81	82	83								
Panel Width	33-7/16"	33-7/8"	34-5/16"	34-3/4"	35-3/16"	35-5/8"	36-1/16"								

Panel widths indicated are for gratings with 3/16" thick bearing bars. For 1/8" thick bearing bars deduct 1/16" from the stated values.

■ Indicates stock panel widths.